


Product survey

Chapter 15


Area- and security lighting



ComfortVision SNF111 15.4




Diamant SNF300Y 15.6




SNF210 15.8



Tempo 1 MWF/SWF130 15.10



Tempo 2 MWF/SWF230 15.12



Tempo 3 MWF/SWF330 15.14



MVF415 15.16



QVF415/416/417 15.17



FGC113Y 15.19












































FWC110/120/121 15.20



FCC110/120 15.21

Technical Overview - Area- and security lighting

Luminaire	page	Dimensions max. HxWxD (mm)	Weight (kg)	IP value	Gear integrated (i) separate (s)	Insulation class	Ambient temperature outdoor	Drag factor	Max. windage area (m2)	Availability barndoors/ louvres
SNF111 	15.4	350x760x510	23	55	s	I	35	1.0	0.19	-
SNF210 	15.8	205x440x630	14.1/16.2	55	i/s	II	35	0.48	0.12	-
SNF300Y 	15.6	320x450x300	8.1/10.6	55	i/s	II	35	-	0.14	●
Tempo										
MVF130 	15.10	390x301x118	4.9	65	i	I	25	-	0.105	●
MVF230 	15.12	399x341x156.5	6.9	65	i	I	35	-	0.117	●
MVF330 	15.14	481x438x180	9.2	65	i	I	35	-	0.186	●
MVF415 	15.16	360x187x210	3.05	65	i	I	35	-	0.06	●
QVF415 	15.17	275x187x130	1.3	55	-	I/II	35	-	0.028	●
QVF416 	15.17	370x320x176	3.4	55	-	I/II	35	-	0.075	●
QVF417 	15.17	370x390x176	4.0	55	-	I/II	35	-	0.084	●
X/FGC113Y 	15.19	302x170x169	2.0	55	-	I	35	-	-	-
FWC110 	15.20	110x242x136	0.9	55	-	II	35	-	-	-
X/FWC120 		134x282x178	1.3							
X/FWC121 		180x160x290	1.7							
FCC110 	15.21	103x242x122	0.9	55	-	II	35	-	-	-
X/FCC120 		150x280x160	1.3							

Luminaire	page	Suitable lamp types								
		Halogen	PL-S	PL-C	SOX	SON(-T) PLUS	SDW-T	HPI-T	CDM-TD	MHN-TD
										
SNF111 	15.4	-	-	-	-	●	-	●	-	-
SNF210 	15.8	-	-	-	-	●	-	●	-	-
SNF300Y 	15.6	-	-	-	-	●	-	●	-	-
Tempo										
MVF130 	15.10	-	-	-	-	●	-	-	●	●
MVF230 	15.12	-	-	-	-	●	●	-	-	●
MVF330 	15.14	-	-	-	-	●	-	●	-	-
MVF415 	15.16	-	-	-	-	-	-	-	-	●
QVF415 	15.17	●	-	-	-	-	-	-	-	-
QVF416 	15.17	●	-	-	-	-	-	-	-	-
QVF417 	15.17	●	-	-	-	-	-	-	-	-
X/FGC113Y 	15.19	-	●	●	●	-	-	-	-	-
FWC110 	15.20	-	●	-	-	-	-	-	-	-
X/FWC120 		-	-	●	●	-	-	-	-	-
X/FWC121 		-	-	-	●	●	-	-	-	-
FCC110 	15.21	-	●	-	-	-	-	-	-	-
X/FCC120 		-	-	-	●	●	-	-	-	-